

HUSQVARNA 120iTK4-H without battery and charger

Husqvarna 120iTK4 battery pole hedge trimmer combines petrol performance with zero direct emission and quiet operation. 120iTK4 is a Telescopic pole product, which means that you can combine the "body" of the machine with either a hedge trimmer or a pole saw attachment. This makes it a versatile and convenient tool for several operations depending on the task at hand. Equipped with a telescopic tube with up to 4m reach and split shaft for easy transportation. Adjustable 7 angled cutting deck for a convenient cutting position when cutting sides and hedges with different heights.



Telescopic tube

The tube has a telescopic function for quick cutting height adjustment



Quiet operation

The low noise provides a comfortable work situation and low disturbance for others.

savE™

Choose between normal or savE™ mode, depending on conditions, for maximum power or maximum runtime. Either way, you'll always get a perfect result.

Articulated cutting deck

Articulated cutting deck for greater versatility and less tiring work.
Adjustable in 7 angels for convenient cutting position when cutting sides, odd angles, inaccessible areas sides or hedges with different heights.



FEATURES

- Choose savE[™] mode for maximum runtime
- Quiet operation
- Telescopic tube for quick cutting height adjustment
- Articulated cutting deck adjustable in 7 angels for convenient cutting position
- Split the product in half for easy transportation and storage.
- Automatically shut down when left unattended
- The batteries within our system are built to be used over a long time, are quick to recharge and even quicker to swap for continuous use
- 100 200 Series battery products have a compact, slimmed-down design for excellent ergonomics.

Technical Specifications BATTERY	
Battery charger	Not included
Battery type	Li-lon
Battery voltage	36 V
lumber of batteries included	0
CAPACITY	
Cutting speed	2800 cut/min
eeth opening	20 mm
IMENSIONS	
rticle gross weight	7000 g
vrticle net weight	5400 g
ull length, including cutting equipment	287 cm
inife Length	50 cm
ecommended maximum twig diameter	15 mm
/eight (excl. battery)	4.525 kg
NGINE	
ear ratio	13.8
lear ratio fotor type	PMDC (2 brushed)
QUIPMENT	i mbc (z brusileu)
	0.0
rrive gear angle echnical Platform	0° HEC-17-28
Connectivity	Not applicable
UBRICANTS	
lower/fuel type	Battery
ACKAGING	
Packaging height	185 mm
Packaging length	1400 mm
Packaging volume	56.98 dm ³
Packaging width	220 mm
Pallet layers	12
Quantity in Master pack	1
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	Og
Paper	300 g
Paper + Cardboard total	2070 g
E foil	5 g
E total	5 g
ET total	2 g
Plastic foil	5 g
Plastic rigid	0 g
Plastic total	5 g
S/EPS/HIPS total	0 g
OUND AND NOISE	
ound power level, guaranteed (LWA)	94 dB(A)
ound power level, measured	91.32 dB(A)
ound pressure (15m)	71.32 dB(A)
ound pressure level at operators ear	81.3 dB(A)
IBRATIONS	
aily Vibration (Aeqv)	1.223 m/s ²
aily Vibration Exposure (A8)	1.223 m/s ²
ally Vibration Time (Time factor)	3h
quivalent vibration level (ahv, eq) front handle	1.223 m/s ²
quivalent vibration level.(ahv, eq), front handle, collapsed	1.223 m/s ²
quivalent vibration level (ahv, eq) rear handle	0.816 m/s ²
quivalent vibration level.(ahv, eq), rear handle, extended	0.816 m/s²
/ibrations handlebar	1.223 m/s ²