



Husqvarna 322iHD60

This durable battery hedge trimmer delivers high-quality cuts at high capacity. Its lightweight, ergonomic design has a balanced rear handle and a mode selector to adapt power and runtime to the job at hand. Experience premium utility with an advanced digital interface, ruggedised hard-top LED buttons and compact size and weatherproof IPX4 classification. Part of the Husqvarna BLi-X 36V battery system range for great flexibility between Husqvarna's wide range of superior battery garden tools.



User friendly keypad

We have thoughtfully designed our products with an easy to operate and use intuitive keypad. Ensuring you can optimise your time and the performance of your product with the simple touch of a button. Equipped with LED indicators showing battery status and ruggedised hard top buttons for improved control.



3-Speed mode maximise your runtime

The 3-speed mode allows you to maximise your runtime by adjusting the power output to the current working conditions.

Low carbon emissions

By choosing this product, you can feel confident that it produces lower carbon emissions during active use compared to a traditional petrol product. This battery-driven product does not emit any CO during use while still providing the power and quality that you expect from a Husqvarna product. However, it's important to note that CO emissions are generated during other stages of the product's lifecycle, such as production, charging and end-of-life disposal.



Automatic shutdown

The product is automatically shut down when left unattended which prolongs the life of the battery, and also lower the risk for injuries when left unattended.



FEATURES

- This product does not emit CO emissions during use.
- 3-Speed mode
- We have thoughtfully designed our products with an easy to operate and use intuitive keypad.
- Automatically shut down when left unattended
- Able to be used in all Husqvarna battery tools, our lithium-ion batteries are durable, easy to swap and recharge quickly
- Weatherproof (IPX4) - Use in all weather conditions
- Compact and lightweight design for more comfortable use

| Technical Specifications | |
|---|----------------------|
| BATTERY | |
| Battery | No |
| Battery charger | Not included |
| Number of batteries included | 0 |
| CAPACITY | |
| Cutting speed | 3500 cut/min |
| Teeth opening | 30 mm |
| DIMENSIONS | |
| Article gross weight | 5210 g |
| Article net weight | 3670 g |
| Full length, including cutting equipment | 112 cm |
| Knife length | 60 cm |
| Weight (excl. battery) | 3.3 kg |
| ENGINE | |
| Gear ratio | 10.4 |
| Motor type | BLDC (brushless) |
| EQUIPMENT | |
| Drive gear angle | 0° |
| Connectivity | Not applicable |
| LUBRICANTS | |
| Power/fuel type | Battery |
| PACKAGING | |
| Packaging height | 206 mm |
| Packaging length | 1410 mm |
| Packaging width | 304 mm |
| Quantity in Master pack | 1 |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 0 g |
| Paper + Cardboard total | 0 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 0 g |
| Plastic total | 0 g |
| PS/EPS/HIPS total | 0 g |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 98 dB(A) |
| Sound power level, measured | 96 dB(A) |
| Sound pressure level at operators ear | 85 dB(A) |
| VIBRATIONS | |
| Equivalent vibration level (ahv, eq) front handle | 2.3 m/s ² |
| Equivalent vibration level (ahv, eq) rear handle | 2.8 m/s ² |

ACCESSORIES



BLI20 BATTERY
967 09 17-01



40-C80
970 48 78-05



PREMIUM EARMUFFS WITH
HEADBAND
505 66 53-04



PROTECTIVE GLASSES - CLEAR X
544 96 37-01



GLOVES, FUNCTIONAL LIGHT
VENT
529 88 01-07



GLOVES, FUNCTIONAL LIGHT
VENT
529 88 01-08



GLOVES, FUNCTIONAL LIGHT
VENT
529 88 01-09



GLOVES, FUNCTIONAL LIGHT
VENT
529 88 01-10



GLOVES, TECHNICAL GRIP
529 88 03-07



GLOVES, TECHNICAL GRIP
529 88 03-08



GLOVES, TECHNICAL GRIP
529 88 03-09



GLOVES, TECHNICAL GRIP
529 88 03-10



GLOVES, TECHNICAL GRIP
529 88 03-12



BATTERY BAG
585 37 18-01



PROTECTIVE GLASSES - SUN X
544 96 37-03



BATTERY BELT FLEXI -
CONNECTOR KIT
590 77 67-03