



Husqvarna KLIPPO LB 548SQe

KLIPPO LB 548SQe, a compact and dedicated BioClip® mower with front-wheel drive for commercial use. The standard sized 48 cm cutting deck makes it to a perfect solution for complex and narrow areas or as a complementary trimming tool for ride-on or robotic mowers. The model is built on the highly respected KLIPPO platform, well-known for outstanding durability and reliable performance. Equipped with the fully commercial and high-specified Husqvarna HS 166AP engine, cast aluminium decks and an ergonomic side-adjustable and effective anti-vibrated handle system, which help the model fulfil A(8) EN836. KLIPPO LB 500 Series, commercial models with outstanding performance and durability for a long-term relation.



Husqvarna HS 166AP engine

HS 166AP, a powerful and fully commercial walk-behind engine from Husqvarna. Designed for high reliability and easy starting. High specified components to withstand tough daily usage and for guarantee longest possible service-life.




Side adjustable handlebar

The handlebar is adjustable both horizontally and vertically for optimum working positions and improved ergonomics.

Aluminium chassis

Heavy-duty, cast aluminium chassis provides increased strength and longer life.



Stainless steel rims

8-inch stainless steel rims with double-sealed bearings. Rubber tyres provide deeper tread depth for increased traction and a more comfortable drive.



FEATURES

- Cast aluminium chassis for longer service life
- Side adjustable handlebar for optimum user position
- A powerful and fully commercial walk-behind engine from Husqvarna. Designed for high reliability and easy starting.
- 8-inch steel rims with double-sealed bearings for longer service life.
- Central cutting height adjustment
- BioClip®

Technical Specifications	
BATTERY	
Battery capacity	0 Ah
Battery type	--
CAPACITY	
Net power at preset rpm	2900 rpm
Power output	2.75 kW
DIMENSIONS	
Article gross weight	38000 g
Article net weight	34500 g
Collector volume	0 l
Cutting width	48 cm
Cylinder displacement	166 cm ³
Handle height adjustment	2 Step
Weight	34.5 kg
Wheel size, Front	203 mm
Wheel size, Rear	203 mm
Wheelbase	52 cm
ENGINE	
Cylinder displacement	166 cm ³
Electrode gap	0.75 mm
Engine brand	Husqvarna
Engine cooling	Air
Engine name	HS 166AP
Fuel tank volume	1.5 l
Spark plug	Husqvarna HQT-7
EQUIPMENT	
Air filter type	Dual element
BioClip® kit	Not available as accessory (NOT AVAILABLE)
BioClip® plug	N/A
Blade brake clutch (BBC)	No
Blade type	Mulcher blade
CLG Product (Calc)	Yes
Collector	No
Collector type	None
Collector volume	0 l
Deflector	No
Drive control	Lever
Drive system	Self-propelled, single speed
Drive wheels	Front
Foldable handle	No
Handle type	Anti-vibrated
Lawnmower drive type	Front-wheel drive
Side adjustable handle	Yes
Soft grip	Yes
Throttle control	No
Water hose connection	No
Wheel bearing, front/rear	Yes/Yes
Connectivity	Not applicable
LUBRICANTS	
Engine lubrication type	Splash
Fuel consumption	407 g/kWh
Fuel consumption	0.023 l/min
Oil filter	No
Power/fuel type	Petrol
MATERIALS	
Cutting deck material	Aluminium
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
Rims, material	Steel
PACKAGING	
Packaging height	479 mm
Packaging length	857 mm

Technical Specifications

Packaging width	525 mm
Quantity in Master pack	1

SOUND AND NOISE

Sound power level, guaranteed (LWA)	93 dB(A)
Sound power level, measured	92 dB(A)
Sound pressure level at operators ear	79 dB(A)

VIBRATIONS

Vibrations handlebar	4 m/s ²
----------------------	--------------------