

Husqvarna 215iHD45 without battery and charger

Husqvarna 215iHD45 is a double-sided battery hedge trimmer, ideal for any type of hedge. Lightweight and well-balanced, this battery hedge trimmer is very easy to start and use, built with premium quality in design, cutting performance, and durability. Equipped with our updated digital user interface, an all-metal gearbox, and a maintenance-free brushless electric motor powerful enough to cut even the thicker branches.



Low Carbon Emissions

By choosing this product, you can feel confident that it produces lower carbon emissions during active use compared to a traditional petrol product. This battery-driven product does not emit any CO during use while still providing the power and quality that you expect from a Husqvarna product. However, it's important to note that CO emissions are generated during other stages of the product's lifecycle, such as production, charging and endof-life disposal.

Automatic shutdown

The product automatically shuts down when left unattended, extending battery life and reducing injury risk.



Efficient Brushless Motor

Brushless motor for higher efficiency, longer lifetime, and less maintenance compared to brushed motors. Since there are no brushes, friction is eliminated, no energy is lost, and the motor runs cooler. This also eliminates the need for maintenance or replacement of worn brushes, and you can benefit from improved performance and higher torque.

User friendly keypad

We have thoughtfully designed our products with an easy to operate and use intuitive keypad. Ensuring you can optimise your time and the performance of your product with the simple touch of a button. Equipped with LED indicators showing battery status and ruggedised hard top buttons for improved control.



FEATURES

- This product does not emit CO emissions during use.
- We have thoughtfully designed our products with an easy to operate and use intuitive keypad.
- The product automatically shuts down when left unattended, extending battery life and reducing injury risk.
- Brushless motor for higher efficiency, longer lifetime and less maintenance compared to brushed motors.
- SavE[™] mode maximises the run time by lowering the rpm and is ideal for tasks that do not require full power.
- Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use.
- Compact, lightweight design for comfortable, ergonomic use and less strain on the body.
- The low noise level contributes to a pleasant working environment and minimal disturbance to the surroundings.
- The battery is placed horizontally through the machine to reduce the risk of dirt and water getting into the battery compartment.

| INTERYNoRetary pranticatorNoRetary pranticatorNoRetary pranticatorNoRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorD21gRetary pranticatorDCAPACITYInternet Califor pranticatorCapacity pranticatorDCapacity p | Technical Specifications | |
|--|------------------------------|----------------------|
| BitspMichadBitspMABitspMainBitsp | BATTERY | |
| bitterMcBatter77 agBatter yrigh14 ndBatter yrigh16 ndBatter yrigh35 VNurtier of batteris telided30 valueCatter gased30 valueCatter gased30 valueDatter stelladed31 mnDatter stelladed440 gAntic pres waft440 gAntic pres waft440 gAntic pres waft25 nnCatter gased120 cnEllength notidig dating agapers25 nnRole starty25 nnWegt (est starty)25 nnEllength notidig dating agapers31 mnMotter on waft45 nnKole starty25 nnWegt (est starty)25 nnEllength notidig dating agapers30 ndMotter on waft31 ndMotter on waft31 ndMotter on waft31 ndEllength notidig dating agapers30 ndWegt (est starty)25 ndEllength notidig dating agapers30 ndEllength notidig dating ag | Battery | No |
| Bathery pay07.9 (a)Bathery type1400Bathery type307.0 (a)Bathery type0CAPACTY | Battery charger | Not included |
| Bathery pay07.9 (a)Bathery type1400Bathery type307.0 (a)Bathery type0CAPACTY | Battery manufacturer | BMZ |
| Bathery tokingsBy VNumber of table instruct0CAPACITY | | 0.7 kg |
| Nurke rokateries rounded0CARACTY200 mar/mColling speed200 mar/mElest speen200 mar/mElest speen20 marElest speen (Speen20 marEles | Battery type | Li-lon |
| CAPACIYSummationLeft sport regin3000 summationLeft sport regin3000 summationDirect sport regin3000 summationPURSISON4860 gArtike stressing4860 gArtike stressing32 LgRecomescing stressing32 LgRecomescing stressing32 LgBrown32 LgBrown32 LgCorr stressing32 LgCorr s | Battery voltage | 36 V |
| Curring speed300 nu/mDiversions337 numDiversions********************************* | Number of batteries included | 0 |
| Tenth opening.38mmPrices priss weight44k01 gArtices priss weight44k01 gArtices priss weight102 cmFall length includies cuting sequences.45cmFall length includies cuting sequences.45cmKrole length45cmKrole length45cmKrole length45cmKrole length32 lengthBearn mode durations to g darables.32 lengthKrole length32 lengthBearn Mode typeBabC (functions)Bearn Mode typeBabC (functions)Bearn Mode type80 concentrations)Bearn Mode type90 concentrations)Bearn Mode ty | CAPACITY | |
| Tenth opening.38mmPrices priss weight44k01 gArtices priss weight44k01 gArtices priss weight102 cmFall length includies cuting sequences.45cmFall length includies cuting sequences.45cmKrole length45cmKrole length45cmKrole length45cmKrole length32 lengthBearn mode durations to g darables.32 lengthKrole length32 lengthBearn Mode typeBabC (functions)Bearn Mode typeBabC (functions)Bearn Mode type80 concentrations)Bearn Mode type90 concentrations)Bearn Mode ty | Cutting speed | 3000 cut/min |
| DMRSNOSI44.00Arcle pres weight44.00Arcle pres weight526.00Construction of the sequence526.00Find length includic outing expresent526.00Recommende materiants hing dameter52.00Recommende materiants hing dameter50.00Recommende materiants hing dameter5 | | |
| Artise rate weigh 2560 g Dil length rolling cutting cuttin | | |
| Artise rate weigh 2560 g Dil length rolling cutting cuttin | Article gross weight | 4480 g |
| Ind langth including during augment102 cmFord langth45 cnRecommended maximum two duringter25 mmWeight (act batter)32 kgENGNE13Cont ratio13Matter typeBCC (trusthess)EQUIPANT20°Contraction20°Packagn phight180 rmPackagn phight180 rmPackagn phight180 rmPackagn phight180 rmPackagn phight19Packagn phight100 rmPackagn phight00 rmPackagn phight00 rmPackagn phight00 rmPackagn phight00 r | | |
| Knils kraft45 cmWeight (scit batray)32 kgBecommender navium bing damlet32 kgENGNE | | |
| Recommended maximum tog dameter 25 mm Weight (and Laterny) 23 log ENGINE 13 Gan ratio 13 Motor type BLDC (brushless) EQUIPMENT 0° Connectivity Not applicable UBBECANTS 8 Proceeding 163 mm Packaging length 163 mm Packaging length 160 mm Packaging usedth 1000 mm Packaging usedth 00 g Packaging usedth 00 g Packaging usedth 00 g Packaging usedth 0 g Packaging use | | |
| Weight (ack battery)22kgENGINE-Cert ratio13Motor typeBLD (trusthes)EUUPPAET-Drive gear angle20*ConnectivityNot applicableUBREANTS-Power Alial typeBateryPAckaging height183 mmPackaging height1600 mmPackaging height1600 mmPackaging height050 mmPackaging height050 mmPackaging height050 mmPackaging height050 mmPackaging height09Packaging height09Packaging height09Packaging height09Packaging height09Packaging height09Packaging height09Packaging height09Packaging height09Packaging wolth09Packaging wolth09Packa | | |
| ENNIMEIGen ratio13Motor typeBDC (brushless)EQUIPMENTDEQUIPMENT0°ConnectivelyNot appleableUBRICATSEPackaging peightBataryPackaging peight183 mmPackaging peight183 mmPackaging peight00° mmPackaging peight00° mmPackaging peight050 mmPackaging peight050 mmPackaging peight050 mmPackaging peight050 mmPackaging peight09 mmPackag | | |
| Ges ratio 13 Motor type BLDC (bruchlesc) EUUPMENT 20* Drive ges angle 20* Connectivity Not applicable LUBRICANTS Battery Packaging height 183 rm Packaging length 1060 rm Packaging volume 49 dm³ Packaging volume 49 dm³ Packaging volume 49 dm³ Packaging volume 255 rm Ocantity in Master pack 1 Matter table 0 Meta total 0g Meta total 0g Packaging volum 0g Other pack rigid 0g Packaging volume 0g Packaging volume 255 rm Ocantity in Master pack 1 Matter total 0g Op 0 Packaging volume 0g Packaging v | | • |
| Motor type BUC (Durahles) EQUIPMENT Connectivity Drive gear angle 20 ° Connectivity Natappicable UBRICANTS Image: Connectivity PACAGING Entry PACAGING Image: Connectivity Packaging length 183 mm Packaging length 183 mm Packaging volth 255 mm Connectivity 255 mm Open of the set pack 1 MATERIALS 0 g Master pack Paper + Cardboard 0 g Open of the plastic rigit 0 g Paper 0 g Paper 0 g Paper 0 g Pastic rigit 0 g Pastic rold 0 g Pastic rold 0 g Pastic rold 0 g Pastic rold 0 g | | 13 |
| EQUIPMENTImage: angleDrive gear angle20 °ConnectivityNet applicableLUBRICANTSImage: anglePACKAGINEImage: anglePACKAGINE183 mmPackaging length1800 mmPackaging length1000 mmPackaging length49 dm³Packaging length255 mmOuantity in Master pack1Master pack Roper - Cardboard0 gMaster pack Roper - Cardboard0 gMaster pack Roper - Cardboard0 gMaster pack Roper - Cardboard0 gPackaging volume9 GPackaging volume0 gPackaging volume0 gPackaging volume0 gDearity in Master pack1Coantity in Master pack0 gDearity in Master pack Roper - Cardboard0 gPackaging volume0 gPackaging volume0 gPaper0 gCoantity in Master pack Roper - Cardboard total0 gPaper0 gPaper0 gPather ingid0 gPaper0 gPastic rigid0 gPast | | |
| Drive gear angle 20* Connectivity Net applicable UBRICANTS Battery PACKAGING Battery PACKAGING 183 mm Packaging length 1050 mm Packaging length 1050 mm Packaging length 255 mm Packaging width 255 mm Quantity in Master pack 0 g Master pack Paper + Cardboard 0 g Paper - Cardboard total 0 g Paper - Cardboard total 0 g Paper - Cardboard total 0 g PE total 0 g PE total 0 g PStPES/HIPS total 0 g Sourd power level quaranteed (UMA) 0 gd(A) Sourd power level quaranteed (UMA) 0 dB(A) Sourd power level at quaranteed (UMA) 0 dB(A) Sourd power level at quaranteed (UMA) 0 dB(A) Sourd power level at quaranteed (UMA) 0 dB(A) | | |
| Connectivity Not applicable LUBRICANTS PAckAging Battery PAckAging height 183 mm Packaging height 1060 mm Packaging height 1060 mm Packaging ustume 49 dm³ Packaging with 255 mm Quantity in Master pack 1 MATERIALS 0 Master pack 0 Paper 0 Paper - Cardboard total 0 Paper - Cardboard total 0 Paper - Cardboard total 0 Pack fight 0 | • | 20.8 |
| LUBRICANTS Battery Power/Just type Battery PackAging height 183 mm Packaging height 183 mm Packaging volume 49 dm³ Packaging volume 0 g Master pack: Paper + Cardboard 0 g Paper + Cardboard total 0 g Paper + Cardboard total 960 g Paper + Cardboard total 0 g Pastic field 0 g Pastic field 0 g Pastic field 0 g Pastic field 0 g Sound power level quaranteed (tWA) 90 dB(A) Sound power level quaranteed (tWA) 0 del(A) | | |
| Power/fuel type Battery Packaging height 183 mm Packaging height 1060 mm Packaging ingth 1060 mm Packaging volume 49 dm³ Packaging volume 49 dm³ Packaging with 255 mm Quantity in Master pack 1 MATERIALS 0 Master pack Raper + Cardboard 0g Paper 0g Paper 0g Paper 0g Paper 0g PE total 0g PE total 0g Pastic total 0g Sound power level, quaranteed (UMA) 0 dB(A) | | Not applicable |
| PACKAGING Indexter space Packaging ing hight 183 mm Packaging ing hight 1060 nm Packaging ing hight 49 dm ³ Packaging ing hight 49 dm ³ Packaging ing hight 255 mm Quantity in Master pack 1 MATERIALS 0 Master pack Paper + Cardboard 0 g Master pack Paper + Cardboard 0 g Paper 0 g Paper 0 g Pastic rigid 0 g Paper + Cardboard total 0 g Paper + Cardboard total 0 g Paper + Cardboard total 0 g Pastic rigid 0 g Pastic rigid 0 g Pastic rold 0 g Sound power level guarantee (UMA) 90 dB(A) Sound power level guarantee (UMA) 90 dB(A) Sound power level guarantee (UMA) 0 dB(A) Sound power | | |
| Packaging height 183 mm Packaging yolume 49 dm³ Packaging volume 49 dm³ Packaging volume 255 mm Quantity in Master pack 1 Matter pack Paper + Cardboard 0g Metal total 0g Ober plastic rigid 0g Paper + Cardboard total 9g0 g Paper + Cardboard total 9g0 g Paper + Cardboard total 0g Pastic fold 0g Pastic fold 0g Paper + Cardboard total 0g Paper + Cardboard total 0g Pastic fold 0g Sound power level, guaranteed (UWA) 90 dB(A) Sound power level, masured 87 dB(A) Sound power level, acparateed at operators ear 79 | | Battery |
| Packaging length 1060 mm Packaging volume 49 dm³ Packaging volume 255 mm Quantity in Master pack 1 MATERIALS 0 Master pack Apper + Cardboard 0 g Metal total 0 g Other typestic rigid 0 g Paper 0 g Paper + Cardboard total 960 g Paper + Cardboard total 960 g Pet total 0 g Pet total 0 g Pastic rigid 0 g Pet total 0 g Pastic total 0 g Sound power level, guaranteed (UWA) 9 odf(A) Sound | | |
| Packaging volume 49 dm³ Packaging width 255 mm Quantity in Master pack 1 MATERIALS 0 g Master pack Paper + Cardboard 0 g Master pack Paper + Cardboard 0 g Other plastic rigid 0 Paper 0 g Paper / Cardboard total 9 60 g PE total 0 g PE total 0 g Plastic rojid 0 g Plastic total 0 g Pastic rojid 0 g Plastic total 0 g Plastic total 0 g Pastic total 0 g Plastic total 0 g Plastic total 0 g Plastic total 0 g Sound power level guaranteed (LWA) 0 g dB(A) Sound power level aperators ear 79 dB(A) Vibration (Agery) 21 m/s ² Daily Vibration (Agery) 21 m/s ² Daily Vibration Inver (Aw, eq) front handle 21 m/s ² Daily Vibration Inver (Aw, eq) front handle 21 m/s ² <t< td=""><td></td><td></td></t<> | | |
| Packaging width 255 mm Quantify in Master pack 1 MATERIALS 0 g Master pack Paper + Cardboard 0 g Metal total 0 g Other plastic rigid 0 g Paper 0 g Paper + Cardboard total 960 g Paper + Cardboard total 0 g PE total 0 g PE total 0 g Plastic rigid 0 g Plastic roll 0 g Plastic roll 0 g Plastic roll 0 g Plastic total 0 g Plastic roll 0 g Plastic roll 0 g Plastic total 0 g Sound power level, guaranteed (LWA) 0 g dE(A) Sound power level, masured 87 dB(A) Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, at operators ear 79 dB(A) Sound power level, dat operators ear 79 dB(A) VBRATIONS 21 m/s² Daily Vibration (Aeqv) 21 m/s² Daily Vi | | |
| Quantity in Master pack 1 MATERIALS 0g Master pack Paper + Cardboard 0g Metal total 0g Other plastic rigid 0g Paper 0g Paper + Cardboard total 960 g Pefer 0g Paper + Cardboard total 960 g PE total 0g PE total 0g Petotial 0g Pastic foil 0g Pastic total 0g Pastic total 0g PS/PS/HIPS total 0g Sound power level, quaranteed (LWA) 90 dB(A) Sound power level, assured 87 dB(A) Sound pressure lusarateed (LWA) 0 dB(A) Sound pressure luser at operators ear 79 dB(A) Vibration (Aeqv) 21 m/s² Daily Vibration (Aeqv) 21 m/s² Daily Vibration Ineval (Av. eq) (ront handle 21 m/s² Equivalent Vibration Ineval (Av. eq) (ront handle 21 m/s² Equivalent Vibration Ineval (Av. eq) (ront handle 21 m/s² Equivalent Vib | | |
| Matterials Master pack Paper + Cardboard 0 g Metal total 0 g Other plastic rigid 0 Paper 0 g Paper + Cardboard total 960 g PE foil 0 g PE total 0 g PE total 0 g Plastic rigid 0 g PE total 0 g Plastic rigid 0 g Plastic rigid 0 g Plastic rigid 0 g Plastic rigid 0 g Plastic total 0 g Plastic total 0 g Plastic total 0 g SOUND AND NOISE 0 g Sound power level, quaranteed (UWA) 9 dB(A) Sound pressure level at operators ear 79 dB(A) Vibration (Acqv) 21 m/s² Daily Vibration (Acqv) 21 m/s² Daily Vibration Ievel (abv. eq) front handle 21 m/s² Equivalent Vibration Ievel (abv. eq) front handle 21 m/s² Equivalent Vibration Ievel (abv. eq) front handle 21 m/s² Equivalent Vibration Ievel (abv. eq) front handle 21 m/s² | | |
| Master pack Paper + Cardboard 0 g Metal total 0 g Other plastic: rigid 0 Paper 0 g Paper + Cardboard total 960 g Paper + Cardboard total 0 g Paper + Cardboard total 0 g PE total 0 g PE total 0 g PAstic rigid 0 g Pastic rigid 0 g Plastic total 0 g Pastic rigid 0 g Pastic rigid 0 g Pastic total 0 g Sound power level, guaranteed (LWA) 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound pressure level at operators ear 79 dB(A) Vibration (Aeqv) 21 m/s² Daily Vibration (Aeqv) 21 m/s² Daily Vibration level (ahv, eq) front handle 21 m/s² Equivalent vibration level (ahv, eq) front handle 21 m/s² Equivalent vibration level (ahv, eq), rear handle 21 m/s² Equivalent vibration level (ahv, eq), rear handle 21 m/s² Equivalent vibration level (ahv, eq), | | 1 |
| Metal total 0 g Other plastic: rigid 0 Paper 0 g Paper 0 g Paper + Cardboard total 960 g Pef total 0 g PE total 0 g PE total 0 g Plastic foil 0 g Plastic rigid 0 g Plastic rigid 0 g Plastic total 0 g PS/EPS/HPS total 0 g SOUND AND NOISE 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration Time (Time factor) 1 h Daily Vibration Time (Time factor) 1 h Equivalent vibration level (abv, eq) front handle 21 m/s² Equivalent vibration level (abv, eq) rear handle 17 m/s² Equivalent vibration level (abv, eq), rear handle 17 m/s² | | |
| Other plastic: rigid 0 Paper 0 g Paper + Cardboard total 960 g PE foil 0 g PE total 0 g PE total 0 g PE total 0 g PE total 0 g Plastic foil 0 g Plastic foil 0 g Plastic total 0 g PS/EPS/HIPS total 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound power level apperators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration Time (Time factor) 1h Daily Vibration Time (Time factor) 1h Equivalent vibration level (ahv. eq) front handle 21 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 17 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 17 m/s² | | |
| Paper 0 g Paper + Cardboard total 960 g PE foil 0 g PE total 0 g PE total 0 g Pastic foil 0 g Plastic total 0 g Sourd power level, guaranteed (LWA) 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound power level at operators ear 79 dB(A) Vibration Exposure (AB) 21 m/s² Daily Vibration (Aeqv) 1 h Equivalent vibration level, (Aiv, eq) front handle 21 m/s² Equivalent vibration level, (Aiv, eq), rear handle 21 m/s² Equivalent vibration level, (Aiv, eq), rear handle 1 m/s² | | |
| Paper + Cardboard total 960 g PE foll 0 g PE total 0 g PE total 0 g Plastic foll 0 g Plastic foll 0 g Plastic foll 0 g Plastic foll 0 g Plastic fold 0 g Plastic total 0 g SOUND AND NOISE 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, quaranteed (LWA) 90 dB(A) Sound power level at operators ear 79 dB(A) Sound power level at operators ear 79 dB(A) Sound power level at operators ear 79 dB(A) Sound power level at operators ear 21 m/s² Daily Vibration Exposure (A8) 21 m/s² Daily Vibration Time (Time factor) 1h Equivalent vibration level (Ahv, eq) front handle 21 m/s² Equivalent vibration level (Ahv, eq) rear handle 21 m/s² Equivalent vibration level (Ahv, eq) rear handle 17 m/s² | | |
| PE foil 0 g PE total 0 g PET total 0 g Plastic foil 0 g PS/EPS/HIPS total 0 g SOUND AND NOISE | | |
| PE total 0 g PET total 0 g Plastic foil 0 g Plastic foil 0 g Plastic rigid 0 g Plastic total 0 g PS/EPS/HIPS total 0 g SOUND AND NOISE 0 Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, measured 87 dB(A) Sound pressure level at operators ear 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration Exposure (A8) 21 m/s² Daily Vibration Inevel (ahv, eq) front handle 21 m/s² Equivalent vibration level (ahv, eq) front handle, collapsed 21 m/s² Equivalent vibration level (ahv, eq) rear handle 11 m/s² Equivalent vibration level (ahv, eq), rear handle 17 m/s² | | |
| PET total 0 g Plastic foil 0 g Plastic rigid 0 g Plastic rigid 0 g Plastic total 0 g PS/EPS/HIPS total 0 g Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, measured 87 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 1 Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Isved (ahv, eq) front handle 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 1.1 m/s² Equivalent vibration level (ahv, eq) rear handle 1.7 m/s² | | |
| Plastic foil 0 g Plastic rigid 0 g Plastic total 0 g Plastic total 0 g PS/EPS/HIPS total 0 g Sound power level, guaranteed (LWA) 0 g dB(A) Sound power level, guaranteed (LWA) 90 dB(A) Sound pressure (LSm) 0 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration (Aeqv) 21 m/s² Daily Vibration Iteme (1ime factor) 1 h Equivalent vibration level (ahv, eq) front handle 21 m/s² Equivalent vibration level (ahv, eq), front handle, collapsed 21 m/s² Equivalent vibration level (ahv, eq), rear handle 1.7 m/s² Equivalent vibration level((ahv, eq), rear handle, extended 1.7 m/s² | | |
| Plastic rigid0 gPlastic total0 gPs/EPS/HIPS total0 gSOUND AND NOISE0 gSound power level, guaranteed (LWA)90 dB(A)Sound power level, guaranteed (LWA)90 dB(A)Sound power level, measured87 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear79 dB(A)VIBRATIONS2.1 m/s²Daily Vibration (Aeqv)2.1 m/s²Daily Vibration Evel (AN)2.1 m/s²Daily Vibration Evel (Ahv, eq) front handle2.1 m/s²Equivalent vibration level (ahv, eq) front handle, collapsed2.1 m/s²Equivalent vibration level (ahv, eq) rear handle, extended1.7 m/s² | | |
| Plastic total 0 g PS/EPS/HIPS total 0 g SOUND AND NOISE 90 dB(A) Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, measured 87 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 79 dB(A) Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Equivalent vibration level (ahv. eq) front handle 2.1 m/s² Equivalent vibration level (ahv. eq) front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv. eq) rear handle 1.7 m/s² | | |
| PS/EPS/HIPS total 0 g SOUND AND NOISE 90 dB(A) Sound power level, guaranteed (LWA) 90 dB(A) Sound power level, measured 87 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 79 dB(A) Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv, eq) front handle 2.1 m/s² Equivalent vibration level (ahv, eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv, eq), rear handle 1.7 m/s² | | |
| SOUND AND NOISESound power level, guaranteed (LWA)90 dB(A)Sound power level, measured87 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear79 dB(A)VIBRATIONS21 m/s²Daily Vibration (Aeqv)2.1 m/s²Daily Vibration Time (Time factor)1 hEquivalent vibration level (ahv, eq), front handle2.1 m/s²Equivalent vibration level (ahv, eq), rear handle2.1 m/s²Equivalent vibration level (ahv, eq), rear handle, extended1.7 m/s² | | · |
| Sound power level, guaranteed (LWA)90 dB(A)Sound power level, measured87 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear79 dB(A)VIBRATIONS79 dB(A)Daily Vibration (Aeqv)2.1 m/s²Daily Vibration Time (Time factor)1 hEquivalent vibration level (ahv, eq), front handle2.1 m/s²Equivalent vibration level (ahv, eq), rear handle2.1 m/s²Equivalent vibration level (ahv, eq), rear handle1.7 m/s² | | Ug |
| Sound power level, measured87 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear79 dB(A)VIBRATIONS2.1 m/s²Daily Vibration (Aeqv)2.1 m/s²Daily Vibration Time (Time factor)1 hEquivalent vibration level (ahv, eq), front handle, collapsed2.1 m/s²Equivalent vibration level (ahv, eq), rear handle2.1 m/s²Equivalent vibration level (ahv, eq), rear handle, extended1.7 m/s² | | |
| Sound pressure (15m) O dB(A) Sound pressure level at operators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv. eq) front handle 2.1 m/s² Equivalent vibration level (ahv. eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv. eq) rear handle 1.7 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 1.7 m/s² | | |
| Sound pressure level at operators ear 79 dB(A) VIBRATIONS 21 m/s² Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv. eq) front handle 2.1 m/s² Equivalent vibration level (ahv. eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv. eq) rear handle 1.7 m/s² Equivalent vibration level, (ahv. eq), rear handle, extended 1.7 m/s² | | |
| VIBRATIONS Image: Constraint of the system Daily Vibration (Aeqv) 2.1 m/s² Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv. eq) front handle 2.1 m/s² Equivalent vibration level (ahv. eq). front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv. eq) rear handle 1.7 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 1.7 m/s² | | |
| Daily Vibration (Aeqv)2.1 m/s²Daily Vibration Exposure (A8)2.1 m/s²Daily Vibration Time (Time factor)1 hEquivalent vibration level (ahv. eq) front handle2.1 m/s²Equivalent vibration level (ahv. eq), front handle, collapsed2.1 m/s²Equivalent vibration level (ahv. eq) rear handle1.7 m/s²Equivalent vibration level, (ahv. eq), rear handle, extended1.7 m/s² | | \A QR(Y) |
| Daily Vibration Exposure (A8) 2.1 m/s² Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv, eq) front handle 2.1 m/s² Equivalent vibration level (ahv, eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 1.7 m/s² Equivalent vibration level (ahv, eq), rear handle, extended 1.7 m/s² | | |
| Daily Vibration Time (Time factor) 1 h Equivalent vibration level (ahv, eq) front handle 2.1 m/s² Equivalent vibration level (ahv, eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 1.7 m/s² Equivalent vibration level (ahv, eq), rear handle, extended 1.7 m/s² | | |
| Equivalent vibration level (ahv, eq) front handle 2.1 m/s² Equivalent vibration level, (ahv, eq), front handle, collapsed 2.1 m/s² Equivalent vibration level (ahv, eq) rear handle 1.7 m/s² Equivalent vibration level, (ahv, eq), rear handle, extended 1.7 m/s² | | |
| Equivalent vibration level.(ahv. eq). front handle, collapsed 2.1 m/s ² Equivalent vibration level (ahv. eq) rear handle 1.7 m/s ² Equivalent vibration level.(ahv. eq), rear handle, extended 1.7 m/s ² | | |
| Equivalent vibration level (ahv, eq) rear handle 1.7 m/s ² Equivalent vibration level, (ahv, eq), rear handle, extended 1.7 m/s ² | | |
| Equivalent vibration level, (ahv, eq), rear handle, extended 1.7 m/s ² | | |
| | | |
| Vibrations handlebar 1.5 m/s ² | | |
| | Vibrations nandlebar | 1.5 m/s ² |