



Actual product may differ from photo.




#### GO THE DISTANCE

## WITHOUT HAVING TO TAKE A BREAK.



Featuring a comfortable operator platform with first-class suspension that minimizes fatigue to the operator, the V-Ride II™ delivers a natural, intuitive and smooth riding position the entire day. With unrivaled performance, stability and durability, this machine helps keep you in tip-top condition to get the job done day after day, year after year.





# MATTHEW H. Mount Vernon, OH

SCAG OWNER FOR 1 YEAR COMMERCIAL OPERATOR

### WHY DID YOU CHOOSE SCAG?

"Being in the green industry, you need reliable and long-lasting equipment, and that's why I chose Scag. They have excellent support and they are built to last!"



### **FEATURES & SPECIFICATIONS**

- Spacious operator platform with adjustable suspension delivers a smooth ride and reduces operator fatigue.
- Scag® heavy-duty cutter deck spindles with 1½" hardened-steel shaft, cast-iron housing and greaseable, tapered roller bearings provide reliable strength. Spindles covered by a 3-year warranty.
- Strong, reliable Ogura PTO clutch engages and disengages the blades quickly and easily with adjustable air gap for long life. Models with 37 hp or more feature a SoftStart Electric Clutch Controller.
- Powerful and efficient Kawasaki® and Briggs Vanguard® engines provide smooth, reliable power. EFI options deliver exceptional fuel efficiency and dependable performance.
- Heavy-duty canister air filter available on Briggs Vanguard and Kawasaki FX and FX EFI engines.
- Heavy-duty steel frame construction ensures a solid foundation for long life.
- Built-in tie-down points allow for quick and easy transport.
- Large drive tires provide surefooted traction: 20" tires on the 32" and 36" models; 24" tires on the 48", 52" and 61" models.
- Rugged dual hydraulic drive system delivers dependable power with 12 cc Hydro-Gear® pumps with cooling fans; 10 cc pumps on 32" and 36" V-Ride II™.
- Productive ground speeds help get the job done fast: up to 10.5 mph on most models; up to 8.5 mph on 32" and 36" models.
- Large 8-gallon fuel tank (6.75-gallon fuel tank on the 36" and 5-gallon on the 32" models). All models feature large, angled filler neck and fuel gauge for operator convenience.
- Flat-free (semi-pneumatic) front caster tires eliminate downtime and expense caused by flat tires.
- Tiger Eye<sup>™</sup> Advanced Monitoring System keeps a constant, real-time "eye" on important system functions of the V-Ride II. (Specific functions vary by mower model and engine. Not available on 32" or 36" models.)
- The 32" and 36" Advantage™ and the 48", 52" and 61" Velocity Plus™ Cutter Decks provide an unmatched quality-of-cut and a wide, even discharge. Tri-Plate deck tops on 36"-61" models are nearly ½" thick.
- The V-Ride II is covered by a strong 2-year commercial or 3-year/500-hour non-commercial mower warranty.
  See the Scag Limited Warranty Statement for details.
- A variety of accessories are available for the V-Ride II such as:
  - 2-Bag Spindle-Driven Grass Catcher.
  - Side-Mounted Fabric Grass Catcher.
  - Hurricane Plus™ Mulch System.
  - Blade Buddy™.
  - Operator-Controlled Discharge Chute (OCDC).
  - LED Light Kit.



Ergonomic operator controls provide incredible ease of use along with maximum comfort. Intuitive control design minimizes the learning curve for new operators.



Easily change cutting heights in the field with no tools ( $1\frac{1}{2}$ " to  $4\frac{1}{2}$ " in  $\frac{1}{4}$ " increments). Deck can be lifted from the operating position with the pull of a spring-assisted lever.



Easy-to-reach, full-featured instrument panel has ignition key, cutter-deck-engagement switch, throttle, choke and Tiger Eye Advanced Monitoring System. (Tiger Eye not available on 32" and 36" V-Ride II models.)



Extra-large comfort cushion allows for comfortable operation, hour after hour. Adjustable platform suspension further enhances operator comfort.



Comfort cushion and lower panel are removable to allow quick and easy service access to the hydraulic system.