SFM-H Series Mulcher

The European designed COSMO **Bully SFM-H Series Mulchers** come with a tower that hydraulically side shifts and a gearbox rating up to 70hp (max.).

The rear of the deck has a series of height adjustable mulching rakes that hold large prunings (up to Ø 50mm) in the cutting chamber for maximum mulching, which along with the high speed rotor and hammer blades produce a high quality cut finish in vineyards, orchards and pastures.

Refer to page 19 for the benefits of using a flail mulcher.



Code	TSFM160H	TSFM175H	TSFM205H	TSFM220H
Description	Bully SFM160-H Mulcher	Bully SFM175-H Mulcher	Bully SFM205-H Mulcher	Bully SFM220-H Mulcher
Side transmission	Belt drive			
Belts	Four (4) BX type			
Gearbox	70hp, 540rpm with free wheel clutch			
PTO shaft/clutch	Series 4 Series 6			
Skids	Adjustable, three (3) positions			
Rear roller	Ø 140mm, height adjustable			
Finish	Powder coated			
Rotor swing dia. (mm)	380			
Rotor diameter (mm)	160			
Rotor speed (rpm)	2083			
Type of blade	Hammer			
No. of hammers	20	22	26	28
Tower position/offset	Hydraulic side shift (300mm)			
Linkage	Category 1 and 2 (bushes for category 2)			
Guarding	CE compliant			
Overall width (mm)	1770	1920	2220	2370
Working width (mm)	1600	1750	2050	2200
Cutting height (mm)	20 - 105			
Tractor range (hp)	40 - 70	50 - 70	55 - 70	60 - 70
Weight (kg)	420	440	485	510

Parts

17295 Bully SFM Series hammer (each)

Optional

17228 Bully SFM Series Y blade (each) 17229 Bully SFM Series Y blade spacer (each)