



SFM-M Series Mulcher

The European designed COSMO Bully SFM-M Series Mulchers have a fixed, bolt on tower with three (3) mounting positions.

The rear of the deck has a series of height adjustable mulching rakes that hold large prunings (up to Ø 50mm) in the cutting chamber for maximum mulching. This results in a high quality cut finish in vineyards, orchards and pastures.

The COSMO Bully SFM-M Series Mulcher is specifically designed for tractors 30 to 70hp.

Refer to page 19 for the benefits of using a flail mulcher.



Code	TFSFM130M	TFSFM145M	TFSFM160M
Description	Bully SFM130-M Mulcher	Bully SFM145-M Mulcher	Bully SFM160-M Mulcher
Side transmission	Belt drive		
Belts	Three (3) BX type	Four (4) BX type	
Gearbox	70hp, 540rpm with free wheel clutch		
PTO shaft/clutch	Series 4		
Skids	Adjustable, three (3) positions		
Rear roller	Ø 140mm, height adjustable		
Finish	Powder coated		
Rotor swing dia. (mm)	380		
Rotor diameter (mm)	160		
Rotor speed (rpm)	2083		
Type of blade	Hammer		
No. of hammers	16	18	20
Tower position/offset	Fixed/bolt on tower with three (3) mounting positions, 150mm apart		
Linkage	Category 1		
Guarding	CE compliant		
Overall width (mm)	1450	1620	1770
Working width (mm)	1300	1450	1600
Cutting height (mm)	20 - 105		
Tractor range (hp)	30 - 70	35 - 70	40 - 70
Weight (kg)	366	388	412

Parts

17295 Bully SFM Series hammer (each)

Optional

17228 Bully SFM Series Y blade (each)

17229 Bully SFM Series Y blade spacer (each)