

Agroplus 420 Profiline

Specialist Series



Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc turbocharged Intercooled
Liquid/Oil Cooled
Individual Bosch Injection System
96Hp (2005/25/CE)
Torque 373nm
Engine Speed Programming
Up Swept Side Exhaust
90 lt Fuel Capacity

Transmission

45/45 Forward/Reverse Gears
Wet Clutch Powershuttle
Powershuttle Modulation L/h Lever
3 Speed Powershift
Comfort Clutch
Stop and GO System
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock
40 km/h Road Speed

PTO

Independent Hydraulic Rear PTO
Push Button
3 Speed PTO 540/750/1000
1" 3/8 – 6 Spline PTO Shaft
External PTO Button on Guard

Wheel Equipment and Miscellaneous

Adjustable Radial Wheel Equipment
Front 320/85R20 –Rear 380/85R30
Front Weight Frame
2 Carbon Filters

Operator Environment

4 Post Hi Visibility Air Conditioned Cab
Hi Visibility Roof
Ergonomic Controls
Multi Function Digital Dash
Super Deluxe Air Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work Lights
2 Bonnet Front Work Lights
Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
54 L/min Hyd Pump
Separate 41L/min Steering Pump
3 Sets of Remotes with Flow Regulator
Electronic 3PL c/w position & draft controls
External Push button Raise and Lower
Cat 2 Hook Ends
3600 kg lift capacity
Swinging Drawbar – CAT A

Weights & Dimensions

| | |
|--------------|--------|
| Wheelbase | 2230mm |
| Length | 3955mm |
| Total Height | 2430mm |
| Total Weight | 3400kg |

Agroplus 420 Profiline

Specialist Series

Front Linkage + PTO

Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc turbocharged Intercooled
Liquid/Oil Cooled
Individual Bosch Injection System
96Hp (2005/25/CE)
Torque 373nm
Engine Speed Programming
Up Swept Side Exhaust
90 lt Fuel Capacity

Transmission

45/45 Forward/Reverse Gears
Wet Clutch Powershuttle
Powershuttle Modulation L/h Lever
3 Speed Powershift
Comfort Clutch
Stop and GO System
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock
40 km/h Road Speed

PTO

Independent Hydraulic Rear PTO
Push Button
3 Speed PTO 540/750/1000
1" 3/8 – 6 Spline PTO Shaft
External PTO Button on Guard

Wheel Equipment and Miscellaneous

Adjustable Radial Wheel Equipment
Front 320/85R20 –Rear 380/85R30
Front Weight Frame
2 Carbon Filters

Front Linkage & PTO

Front Linkage - 1750kg Capacity
Front PTO – 1000N
Push Button PTO Control
Shock accumulator in Front linkage
Linkage operated via duplicated rear remote



Operator Environment

4 Post Hi Visibility Air Conditioned Cab
Hi Visibility Roof
Ergonomic Controls
Multi Function Digital Dash
Super Deluxe Air Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work Lights
2 Bonnet Front Work Lights
Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
54 L/min Hyd Pump
Separate 41L/min Steering Pump
3 Sets of Remotes with Flow Regulator
Electronic 3PL c/w position & draft controls
External Push button Raise and Lower
Cat 2 Hook Ends
3600 kg lift capacity
Swinging Drawbar – CAT A

Weights & Dimensions

| | |
|--------------|--------|
| Wheelbase | 2230mm |
| Length | 3955mm |
| Total Height | 2430mm |
| Total Weight | 3600kg |

April 2022